

OPERATING & SAFETY GUIDE

MIRROR BAR ILLUMINATED REAR SHELF UNIT

GENERAL SAFETY

Contact us for information and advice on the suitability and safety of this type of equipment.

There is a risk of injury if you do not follow the instructions printed in this guide.

This equipment should only be used by a competent adult who has read and understood these instructions. Anyone with a temporary or permanent disability should seek expert advice before using the equipment.

Keep all children, animals and bystanders away from the set-up area.

Ensure the floor where the unit is to be sited is level and free from trip hazards and is non-slip.

Never set up or use the Mirror Bar Illuminated Rear Shelf Unit if you are ill, tired or under the influence of alcohol or drugs.

Never plug in or operate electrical switches with wet hands. Always switch off and unplug the Mirror Bar Illuminated Rear Shelf Unit RCD protected power lead from the main power supply before dismantling, moving or cleaning.

Check the equipment before use, if it shows signs of damage request a replacement.

ELECTRICAL SAFETY

The Mirror Bar Illuminated Rear Shelf Unit lighting unit is designed to plug directly into a standard 240volt, 13 amp socket.

Make sure the Mirror Bar Illuminated Rear Shelf Unit light unit and power socket are switched off before plugging into the power supply.

If the equipment fails to operate or the power cable or plug become damaged, contact us, do not try to repair it yourself.

Keep the power cable out of harm's way.

Extension leads should be unwound fully, never run them through water or where they may get wet, over sharp objects or where they may be a trip hazard.

The lighting unit is supplied with an RCD (Residual Current Device) power lead to reduce the risk of electric shock.

OPERATING GUIDE

Position the Mirror Bar Illuminated Rear Shelf Unit on a level floor that is free from trip hazards and is non-slip.

Any light replacement can only be carried out by our service team as all lights are hard-wired in.

Keep the power cable out of harm's way. Extension leads should be unwound fully, never run them through water, over sharp objects or where they may be a trip hazard.

Make sure the RCD power lead is disconnected from the power socket before dismantling the unit.